

Technical Data Sheet

Hyunity FCS Process Inks

FEATURES

- International technology
- Fully imported
- Excellent water balance – suitable for both alcohol and non-alcohol dampening systems
- Good scuff resistance

ADVANTAGES

- Fast setting, allowing quick turnaround
- Conforms to ISO Standard 2846 -1 for Shade and Transparency
- Classified as Not Hazardous according to the criteria of Worksafe Australia
- Stays “open” in the ink duct overnight
- Excellent dot sharpness

RANGE

- Available in both Standard and Low Tack versions

RECOMMENDATIONS

- When using Hy-Unity for Laser printing applications, due to the variations in stocks and laser equipment available that may affect job results, we recommend that customers conduct their own tests on alternative stocks and Laser equipment to determine suitability.
- We recommended that for overprinting with UV varnish a suitable primer be used

SHELF LIFE

Toyo recommends that this product be used before 18 months from the date of manufacture.

Further Information: Please contact our Technical Department on 03 9751 7200

Disclaimer The information herein is to the best of our knowledge, correct and complete. Since methods and conditions are beyond our control we do not accept liability for any damages resulting from the use of, or reliance on, this information in inappropriate contexts.

TOYO INK OFFICES ACN 006 294 837

VIC: 29 Garden Street, KILSYTH 3137

NSW: U12 Slough Bus. Park 2 Slough Avenue, SILVERWATER NSW 2128

QLD: 3/43 Prosperity Place, GEEBUNG 4034

NZ: 57E McLaughlin's Road WIRI. MANUKAU CITY, AUCKLAND

PH 03 9751 7200 FAX 03 9728 4099

PH 02 9742 3760 FAX 02 9742 3778

PH 07 3865 7795 FAX 02 3865 8357

PH 0011 64 9 250 444